



Product data sheet Indoor station BSH2012 Receiver, 2-wire

With the BSH2012 Audio which can intuitively be operated SKS sets an actual standard: Without any compromise this indoor station focuses with its design on the essential.

The BSH2012 Audio sets a standard for all SKS basic models in the segment of indoor stations with receiver.

Features

- SKS BUS technology
- Indoor station with receiver, (the ergonomic receiver is held by a magnet; accepting calls by picking up the receiver)
- Key functions: Opening door, adjusting volume of calls and ringtones, muting (ringtone is reactivated automatically after 12 hours), potential-free switching functions possible (via switching actuator 300022 or BUS actuator module 300095, without additional wires)
- Optical call signalisation with LEDs
- Audio privacy function
- One-man installation and programming
- Optional parallel operation of up to 4 indoor stations
- 8 door call and 4 floor call ringtones
- Ringtone volume can be adjusted in 5 steps
- Operation via 6 concave touch keys (allow for an optimal operability at any age)
- Audio and video indoor stations can be combined within one structure
- Surface mounting

Versions

Item no.	Description	Color
200027	BSH2012, Audio, receiver, 2-wire	white

With automatic door opener function		
Item no.	Description	Color
200029	BSH2012, Audio, receiver, 2-wire, with ADO function	white

Technical data

Electrical data	
Voltage a+ / b-	19 – 23 VDC
General data	
Temperature	-10°C to +45°C
Humidity	20% to 90%, non condensing
Housing	Plastic
Measurements (width x height x depth)	89 x 230 x 23 mm
Protection class	IP20