



Product data sheet Indoor station HT4600 Receiver, 2-wire

The HTV4600 reduces the operating elements to the essential. The ergonomic receiver which is kept in position with the help of a magnet enables the user to operate the indoor station intuitively at any age.

Features

- SKS BUS technology
- Key functions: Opening door, adjusting volume of calls and ringtones, muting (ringtone is reactivated automatically after 12 hours)
- Switching functions possible (without additional wires, using switching actuator 300022 or BUS actuator module 300095)
- Optical call signalling with LEDs
- Receiver is held by a magnet (allows for an optimal operability at any age)
- Audio privacy function
- One-man installation and programming
- Parallel operation of up to 4 indoor stations optional
- 8 door call and 4 floor call ringtones
- Ringtone volume can be adjusted in 5 steps
- Optional 6 additional keys for internal call function
- Surface-mounting

Versions

4 keys

Item no.	Description	Color
200009	HT4600 (4 keys), audio, 2-wire	white

4 keys + 6 keys for internal call function

Item no.	Description	Color
200010	HT4600 (10 keys), audio 2-wire	white

Technical Data

Electrical data

Etectificat autu	
Voltage a+/b-	19–23 VDC
General data	
Temperature	-10 °C to +45 °C
Humidity	20 % to 90 %, non-condensing
Housing	Plastic housing
Measurements (width x height x depth)	82 x 193 x 33 mm incl. receiver
Protection type	IP20
